

TECHNICAL DATA SHEET

DECOR HYGIENE+

DECOR HYGIENE+ is specially designed, water borne bactericidal single component hygiene paint for architectural interior walls. DECOR HYGIENE+ is a tough and highly durable self protective paint against the growth of micro-organisms like mold, fungi, yeasts and bacteria. Its anti-microbial system does not leach out, unlike the traditional paints, and it therefore remains safe and active throughout the life of the product.

Conforms to: JIS Z 2801 & ASTM E2180-01



Typical applications

- + Hospitals & nursing homes
- + Food processing units
- + Pharmaceutical plants
- + Schools, colleges class rooms
- + Hotels & restaurants
- + Community halls and other public places

Features & Benefits

- + Water borne single-pack, low odor, rapid drying paint
- + Kills or inhibits the growth of harmful bacteria such as escherichia coli and staphylococcus
- + Excellent stain and scrub resistance
- + Easy to apply with conventional tools
- + High mechanical robustness
- + No fungus, algae, mildews growth on the cured paint film

Technical information

Materials: Single pack modified polyurethane dispersion (pud)

Color: Available in all shades

Recommended DFT: 30-50 micron/coat

Touch dry time: 15-20 min

Recoat time: Min 3 hrs

(depending on air temperature & humidity)

Finish: Semi glossy

Coverage: Approx 120 - 150 sq.ft. / litre in two coats

Cleaning solvent: Water

Recommended dilution (with water only):

~ Brush and roller application: 10-15% by volume

~ Spray application: 15-20% by volume

TECHNICAL DATA SHEET**DÉCOR HYGIENE+**

Application Guidelines**Surface preparation**

Surface must be free from dirt, grease, oils and any other foreign substances. Any flakes of old paint or powdery residues must be scrapped off and cleaned thoroughly by sanding using an emery paper. Algae and fungus on walls to be removed by high pressure water wash or coir brush and apply Bio-Wash fungicidal solution if needed. Fill cracks with suitable crack filling chemicals prior to start the painting job.

Apply PRIMER W2K on well-prepared surface. Apply suitable putty to remove the undulation on the surface. Once the putty dries sufficiently hard smoothen the surface by sanding with emery paper No. 320. Apply one coat of PRIMER W2K on the sanded surface and allow it to dry for 3-4 hrs prior to the application of Hygienecoat+ finish.

Precautions & limitations

- + HYGIENECOAT+ is for Interior use only
- + Do not apply when concrete surfaces or ambient temperatures are below the dew point
- + Material and the substrate temperature should be above 10°C and below 50°C before use
- + Application on direct sunlight and windy situation may affect the paint performance

Product specs

Storage: Store in cool & dry place.

Keep container tightly closed in a secure, upright position. Store in accordance with local regulations.

Packing: 1, 4 & 20 ltr

Shelf life (when stored as recommended): Min 36 months

Mixing and Application

Stir the paint before application and then thin down to applicable consistency with required quantity of potable water. Mix thoroughly till the components become homogenous. Apply the paint liberally with paint brush followed by rollers. Apply 2-3 coats of Hygienecoat+ to achieve the desire opacity as well as finish depending on the shades. Provide 3-4 hrs drying interval in between the coats.

Cleaning

Clean all tools and spillage of paint with water immediately after application.